

Type	Air flow according to ISO 1217 (Annex C-1996)		Motor Power kW	Length mm	Width mm	Height mm	Weight kg
	8 bar (m ³ /min)	10 bar (m ³ /min)					
SONETTO 8	0.75	0.63	5.5	810	650	995	156
SONETTO 10	1.00	0.92	7.5	810	650	995	167
SONETTO 15	1.43	1.31	11	810	650	995	180
SONETTO 8 270L	0.75	0.63	5.5	1533	650	1352	191
SONETTO 10 270L	1.00	0.92	7.5	1533	650	1352	202
SONETTO 15 270L	1.43	1.31	11	1533	650	1352	215
SONETTO 8 500L	0.75	0.63	5.5	1935	650	1483	281
SONETTO 10 500L	1.00	0.92	7.5	1935	650	1483	292
SONETTO 15 500L	1.43	1.31	11	1935	650	1483	305
SONETTO PLUS 8 270L	0.75	0.63	5.5	1533	650	1352	219
SONETTO PLUS 10 270L	1.00	0.92	7.5	1533	650	1352	245
SONETTO PLUS 15 270L	1.43	1.31	11	1533	650	1352	259
SONETTO PLUS 8 500L	0.75	0.63	5.5	1935	650	1483	309
SONETTO PLUS 10 500L	1.00	0.92	7.5	1935	650	1483	335
SONETTO PLUS 15 500L	1.43	1.31	11	1935	650	1483	349



Alup ES99

Straight forward control panel, providing a full set of warnings and maintenance related messages to comfort your daily operation.

Moreover, the ES99 software adjusts the load-no-load time to the actual consumption, preventing the electrical motor from running when not needed.



Compatibility, flexibility, diversity

The SONETTO series is designed with a large variety of versions and models that can be utilized in a large diversity of applications

You can install this series:

- ... as standard compressor



Pictures displayed SONETTO 8-15

In any case, the series sets new standards for its power class with regard to quality, operational safety, service life and user comfort.



- ... mounted on a 270L tank



- ... mounted on a 270L tank with refrigerant dryer



- ... mounted on a 500L tank



- ... mounted on a 500L tank with refrigerant dryer



intelligent compressed air ... everywhere ■ ■ ■ intelligent compressed air ... everywhere ■ ■ ■ intelligent compressed air ... everywhere ■ ■ ■